



We are a company based in the UK



APPLE MACBOOK PRO 15" UP TO 2008 MEMORY INSTALLATION GUIDE

Mr Memory®

WHAT YOU WILL NEED



CLEAR WORKSPACE



CLEAN TOWEL OR BLANKET



NEW MEMORY MODULE(S)



SCREWDRIVER



TO PREVENT ANY POTENTIAL DAMAGE FROM ANTI STATIC ELECTRICITY, YOU SHOULD DISCHARGE YOURSELF FIRST. THIS CAN BE DONE BY TOUCHING A GROUNDED METAL OBJECT - SUCH AS A RADIATOR.

STEP 1

Make sure the MacBook is powered off and all cables have been disconnected.

STEP 2

Turn the MacBook over and lay on t a clean towel or blanket and locate the battery releases on each side of the battery. Slide both latches up to remove the battery.

STEP 3

Remove the screws holding the memorycover in place – there may be 3 or 4 screws depending on the model.



STEP 4

Slide the memory cover towards you, pulling it away from the casing.



STEP 5

To remove any existing RAM, push the levers on the sides of the module away from the module. The module will pop out at an angle.



STEP 6

To install the new memory, align the notch on the gold part of the module with the notch in the slot. Tilt the card and push the memory firmly and evenly into the slot. There will be an audible click when the memory is seated correctly. Do not worry which way the stickers face, as this will differ.

STEP 7

To reassemble the MacBook, reattach the back panel and replace the screws into their locations. Replace the battery, making sure the latch is in the open position. Replace the access door and press the latch into the close position.

IF YOU REQUIRE ANY FURTHER INSTALLATION SUPPORT, PLEASE CONTACT OUR CUSTOMER CARE & SUPPORT TEAM